

CLAIMS

What is claimed is:

SUB
A1

- 1. A method for modifying a virtual object in a haptic virtual environment,
 - 2 comprising:
 - 3 determining a virtual tool comprising a plurality of discrete points for use
 - 4 by the user in the haptic virtual environment;
 - 5 selecting a modification mode for the virtual tool;
 - 6 sensing a location of a user in real space;
 - 7 determining locations of the plurality of discrete points of the virtual tool
 - 8 relative to a location of the virtual object;
 - 9 calculating an interaction force between the virtual tool and the virtual
 - 10 object based on the locations of the plurality of discrete points of the virtual tool
 - 11 and the location of the virtual object;
 - 12 producing a modified virtual object by modifying the virtual object based
 - 13 on the modification mode, the locations of the plurality of discrete points of the
 - 14 virtual tool, and the location of the virtual object; and
 - 15 outputting the modified virtual object.

- 2. The method of claim 1, further comprising the steps of
 - 2 determining a virtual surface for the virtual object; and
 - 3 determining a position and an orientation of the virtual tool by
 - 4 determining the locations of the plurality of discrete points relative to the virtual
 - 5 surface of the virtual object.

- 3. The method of claim 2, wherein the step of determining the virtual surface
 - 2 comprises determining a virtual isosurface for the virtual object.

65000782500

Sub
B2

1 4. The method of claim 1, wherein the virtual object is a volumetric
2 representation.

1 5. The method of claim 4, wherein the volumetric representation comprises voxels
2 comprising density values.

1 6. The method of claim 1, wherein the step of selecting a modification mode for
2 the virtual tool comprises selecting one of a material removal, a material addition,
3 and a material modification mode.

1 7. The method of claim 1, further comprising the step of determining at least one
2 virtual constraint for the movement of the virtual tool.

1 8. The method of claim 7, wherein the step of determining at least one virtual
2 constraint for the movement of the virtual tool comprises determining at least one
3 of a point, curve and surface constraint for the movement of the virtual tool.

1 9. The method of claim 1, further comprising the step of exporting the modified
2 virtual object.

1 10. A system for modifying a virtual object by a user in a haptic virtual
2 environment , the system comprising:

3 a virtual tool comprising a plurality of discrete points for use by the user
4 in the haptic virtual environment, wherein the user selects a modification mode
5 for the virtual tool;

6 a haptic interface device, wherein the haptic interface device senses a
7 location of the user in real space;

8 a modeling application in communication with the haptic interface device,
9 the virtual object, and the virtual tool, wherein the modeling application
10 determines locations of the plurality of discrete points of the virtual tool relative
11 to a location of the virtual object; calculates an interaction force between the

SUB
A2

55009790000

SUB
B4

SUB
A3

14 location, and the location of the virtual surface and the constraint geometry; and
15 constraining an action of the virtual tool based on (i) the constraint geometry, (ii)
16 the virtual surface, and (iii) the position of the virtual tool, and (iv) the haptic
17 interface location.

1 28. The system of claim 27, wherein the constraint geometry is at least one of a
2 constraint point, constraint curve, and a constraint surface.

1 29. The system of claim 27, wherein the modeling application determines the
2 position of the virtual tool by moving the position of the virtual tool to coincide
3 with the haptic interface location.

SUB
A8

1 30. The system of claim 27, wherein the modeling application modifies the
2 virtual object based on the position of the virtual tool.

1 31. The system of claim 27, wherein the modeling application calculates an
2 interaction force among the constraint geometry, the virtual object, and the virtual
3 tool in response to determining the position of the virtual tool.

1 32. The system of claim 27, further comprising a modification mode for the
2 virtual tool selected by the user, and the modeling application modifies the virtual
3 object in response to the modification mode and the position of the virtual tool.

1 33. The system of claim 27, wherein the action of the virtual tool comprises a
2 translation of the virtual tool.

1 34. The system of claim 27, wherein the action of the virtual tool comprises a
2 rotation of the virtual tool.

[Handwritten bracket on the left side of the page, spanning from claim 33 to claim 34]

add
A8

559070" 2844550